Application No. 10/722,316 Amendment dated 09/20/2006 Reply to Office Action of July 7, 2006

03-ASD-159 (EM)

## Amendments to the Claims:

Please amend the claims as indicated below.

## Listing of Claims:

- 1. (Withdrawn) A method of connecting a solenoid to a lead frame comprising: (a) disposing a plurality of connector terminals on the solenoid; (b) disposing a web between a first and second of said terminals; (c) providing a lead frame and forming a plurality of slots in the frame and spacing each slot to correspond to one of said terminals; (d) disposing a pair of projections on the lead frame and locating the projections on opposite sides of said web; and, (e) inserting each of said connector terminals in said corresponding slot and engaging said web with said projections.
- (Withdrawn) The method defined in claim 1, wherein said step of disposing a
  plurality of connector terminals includes forming support stanchions for each of said
  terminals.
- (Withdrawn) The method defined in claim 1, wherein said step of forming a pair of projections includes locating said projections between said slots.
- 4. (Withdrawn) The method defined in claim 1, wherein said step of disposing a web includes forming said projections integrally therewith.
- 5. (Withdrawn) The method defined in claim 4, wherein said step of forming integrally includes molding.
- (Withdrawn) The method defined in claim 1, wherein said step of disposing connector terminals includes forming a stanchion supporting each of said terminals.
- (Currently amended) In combination a solenoid and lead frame assembly comprising:
  - (a) a plurality of connector terminals with a web disposed between a first and

09/20/2006 14:38

Application No. 10/722,316 Amendment dated 09/20/2006 Reply to Office Action of July 7, 2006

03-ASD-159 (EM)

## second of said terminals;

- a lead frame with a pair of discrete projections thereon and a pair of slots (b) each located to correspond to one of said first and second terminals; and
- said lead frame slots engage said terminals with said pair of discrete (c) projections engaging opposite sides of said web.
- (Original) The assembly defined in claim 7, wherein said projections are integrally 8. formed with said lead frame.
- (Original) The assembly defined in claim 8, wherein said projections and said lead 9, frame are integrally molded.
- (Original) The assembly defined in claim 7, wherein said terminals include support 10. stanchions.
- (Original) The assembly defined in claim 10, wherein said support stanchions are 11. integrally molded with said lead frame.
- (Original) The assembly defined in claim 10, wherein said web is integrally formed 12. with said support stanchions.
- (Original) The assembly defined in claim 10, wherein said web and said stanchions 13. are integrally molded with said lead frame.
- (Original) The assembly defined in claim 7, wherein said web is integrally formed 14. with said lead frame.
- (Original) The assembly defined in claim 14, wherein said web and said lead frame 15. are integrally molded.
- (Original) The assembly defined in claim 7, wherein said projections are disposed 16. intermediate said slots.